



TASKalfa 180 standard configuration with optional document processor  
22.4" W x 21.5" D x 26.1" H



TASKalfa 180 with 2 optional paper drawers, low copy stand, and document processor



Easy-to-use control panel allows you to access copy features quickly and efficiently



Easy-to-replace toner containers

### Basic Specifications

Configuration	Black & White Multifunctional System - Standard Copy / Optional GDI Print
Pages Per Minute	Letter: 18 ppm; Legal: 8 ppm; Ledger: 8 ppm
Warm-up Time	17.2 Seconds or Less
First Copy / Print Out Time	5.7 Seconds or Less
Copy Resolution	600 x 600 dpi
Copy / Scan Memory	32 MB RAM
Duplex	Optional Stackless, Statement to Ledger, 17 - 28 lb Bond
Electrical Requirements	120V, 60Hz, 9.0A 220-240V, 50/60Hz, 5.0A
Dimensions / Weight	22.4" W x 21.5" D x 20.9" H / 72.8 lbs (mainframe)
Max Monthly Duty Cycle	20,000 Pages per Month

### Paper Supply

Standard Paper Sources	300 Sheet Universal Drawer, 100 Sheet MPT
Optional Paper Sources	300 Sheet Universal Paper Drawers (PF-420)
Paper Capacity	Standard: 400 Sheets; Maximum: 1,300 Sheets
Paper Size	5.5" x 8.5" - 11" x 17" (Statement to Ledger)
Paper Weight	17 lb Bond - 28 lb Bond; MPT: 13 lb Bond - 90 lb Index
Input Materials	Bond Paper, Recycled Paper, Transparencies, Envelopes
Paper Output	Up to 250 Sheets (Letter)

### Document Processor

Type / Capacity	RADF Type Document Processor / 50 Sheets (Letter)
Copy Scan Speed	22 ipm
Acceptable Originals / Weights	5.5" x 8.5" - 11" x 17" / 13 lb Bond - 90 lb Index

### Duplex

Paper Size	5.5" x 8.5" - 11" x 17" (Statement to Ledger)
Paper Weight	16 - 28 lb Bond
Duplex Modes	Standard 1:2; 2:2; Book:2; 2:1

### Copy Specifications

Image Mode	Text, Photo, Text/Photo, Auto, Manual
Continuous Copy	1 - 999 / Auto Reset to 1
Additional Copy Features	Auto Center, Magnification and Paper Select, Book Mode, Border Erase, Margin Shift, N-Up Copy, Electronic Sort, Sort Mode, Group Mode
Job Management	Job Interrupt, Job Programs, 100 Department Codes (copy only)
Magnification / Zoom	Full Size, 5 Reduction, 5 Enlargement Preset Ratios, 25 - 400% in 1 step increments

### Printer Specifications

Controller	FlexRISC 150MHz
PDLs/Emulations	GDI (Host-based)
Memory	32MB RAM
Fonts	1 Bitmap
Windows OS Compatibility	Windows 2000 / XP / 2003 / Vista
Interfaces	Hi-Speed USB 2.0; Optional 10/100 Base TX
Network Print and Supported Protocols	TCP/IP
Drivers	GDI Driver
Utilities	KMnet Viewer, Status Monitor

### Optional Paper Drawers

Paper Capacity	300 Sheets
Maximum Drawers	Up to three (3) can be installed
Paper Size	5.5" x 8.5" - 11" x 17"
Paper Weight	16 - 28 lb Bond

### Additional Options

IB-110 External Print Server; Platen Cover - E; High / Low Copy Stand
---

Specifications and design are subject to change without notice.  
For the latest on connectivity visit [www.kyoceramita.com](http://www.kyoceramita.com)  
All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA  
©2009 Kyocera Mita America, Inc.  
IC# 855D400218