



TASKalfa 220 standard configuration with optional document processor
22.4" W x 21.5" D x 26.1" H



TASKalfa 220 with 2 optional paper drawers, low copy stand, and document processor



Easy-to-use control panel allows you to access copy features quickly and efficiently



Easy-to-replace toner containers

Basic Specifications

Configuration	Black & White Multifunctional System - Standard Copy / Optional GDI Print
Pages Per Minute	Letter: 22 ppm; Legal: 11 ppm; Ledger: 10 ppm
Warm-up Time	17.2 Seconds or Less
First Copy / Print Out Time	5.7 Seconds or Less
Copy Resolution	600 x 600 dpi
Copy / Scan Memory	32 MB RAM
Duplex	Optional Stackless, Statement to Ledger, 17 - 28 lb Bond
Electrical Requirements	120V, 60Hz, 9.0A 220-240V, 50/60Hz, 5.0A
Dimensions / Weight	22.4" W x 21.5" D x 20.9" H / 72.8 lbs (mainframe)
Max Monthly Duty Cycle	30,000 Pages per Month

Paper Supply

Standard Paper Sources	300 Sheet Universal Drawer, 100 Sheet MPT
Optional Paper Sources	300 Sheet Universal Paper Drawers (PF-420)
Paper Capacity	Standard: 400 Sheets; Maximum: 1,300 Sheets
Paper Size	5.5" x 8.5" - 11" x 17" (Statement to Ledger)
Paper Weight	17 lb Bond - 28 lb Bond; MPT: 13 lb Bond - 90 lb Index
Input Materials	Bond Paper, Recycled Paper, Transparencies, Envelopes
Paper Output	Up to 250 Sheets (Letter)

Document Processor

Type / Capacity	Optional DP-420 Document Processor RADF Type Document Processor / 50 Sheets (Letter)
Copy Scan Speed	22 ipm
Acceptable Originals / Weights	5.5" x 8.5" - 11" x 17" / 13 lb Bond - 90 lb Index

Duplex

Paper Size	5.5" x 8.5" - 11" x 17" (Statement to Ledger)
Paper Weight	16 - 28 lb Bond
Duplex Modes	Standard 1:2; 2:2; Book:2; 2:1

Copy Specifications

Image Mode	Text, Photo, Text/Photo, Auto, Manual
Continuous Copy	1 - 999 / Auto Reset to 1
Additional Copy Features	Auto Center, Magnification and Paper Select, Book Mode, Border Erase, Margin Shift, N-Up Copy, Electronic Sort, Sort Mode, Group Mode
Job Management	Job Interrupt, Job Programs, 100 Department Codes (copy only)
Magnification / Zoom	Full Size, 5 Reduction, 5 Enlargement Preset Ratios, 25 - 400% in 1 step increments

Printer Specifications

Controller	FlexRISC 150MHz
PDLs/Emulations	GDI (Host-based)
Memory	32MB RAM
Fonts	1 Bitmap
Windows OS Compatibility	Windows 2000 / XP / 2003 / Vista
Interfaces	Hi-Speed USB 2.0; Optional 10/100 Base TX
Network Print and Supported Protocols	TCP/IP
Drivers	GDI Driver
Utilities	KMnet Viewer, Status Monitor

Optional Paper Drawers

Paper Capacity	300 Sheets
Maximum Drawers	Up to three (3) can be installed
Paper Size	5.5" x 8.5" - 11" x 17"
Paper Weight	16 - 28 lb Bond

Additional Options

IB-110 External Print Server; Platen Cover - E; High / Low Copy Stand

Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com
All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA
©2009 Kyocera Mita America, Inc.
IC# 855D400219